

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非给予明确授权，否则禁止转让、复制、利用、发布本文件的内容。侵犯者将承担赔偿责任。本公司保留对涉及发明、实用新型和外观设计的所有权利。

FOR-1754 Rev.1.2



2

3


4

5

6



Panel Cut-out



Dimensional tolerance(mm)					Length tolerance(mm)				0.10/10 ±2°
0 ~ 30	>30 ~ 60	>60 ~ 100	>100 ~ 150	>150	0 ~ 5000	5000 ~ 10000	10000 ~ 30000	>30000	
±0.25	±0.35	±0.55	±0.80	±1.10	±55	±105	±205	±505	
额定电压电流/Rated Voltage/Current							1000V/70A		
绝缘电阻/Insulation resistance							≥100MΩ		
插拔次数/Mechanical working life(mating cycles)							100		
耐电压/Withstanding voltage							4250V DC		
使用温度范围/Operating temperature(°C)							-40~+80°C		
防水等级/Levels of protection							IP67		
接线方式/Terminal							Screw		
扭矩力/M4 Screw Torque(N.m)							1.2~1.5		
线径/Wire range							8AWG/10mm ²		
符合RoHS环保要求/Conform to RoHS							Yes		

		SURFACE: /	
		宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD	
NAME: ESS-70A-10-S-OR-00			
DRAWING NO.: /		REV	00
TYPE: CUSTOMER DRAWING		SCALE: 1:1	SHEET 1/1

REV	ECN	DESCRIPTION	DRFT	DATE