

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless authorized in writing. Violations will be liable for compensation. All rights reserved for patent, utility model or design registrations. 除专利、实用新型、外观设计、发明专利、软件著作权、集成电路布图设计专有权、商业秘密和不正当竞争等权利外，本公司保留对涉及发明、实用新型、外观设计、发明专利、软件著作权、集成电路布图设计专有权、商业秘密和不正当竞争等权利的所有权利。

FOR-1755 Rev.1.7

2



3

4





5

6

尺寸公差(mm)					0.05/10 ±1°
0 ~ 30	>30 ~ 60	>60 ~ 100	>100 ~ 150	>150	
±0.20	±0.30	±0.50	±0.70	±1.00	



弯头壳体



Pin Assignments
Front View

技术要求/Technical requirements:	
额定电压/Rated Voltage/Current	250V AC/4A
绝缘电阻/Insulate Resistance	>100MΩ
耐压/Withstanding Voltage	1500V AC 1min
防护等级/Ingress Protection	IP67
插拔寿命/Insertion/Pullout Times	100 Cycles
插拔力/Insertion/Pullout Force	<30N
使用温度范围/Operating temperature(°C)	-25~+105
重点管控符号/Key controlled symbol	*
包装规范/Packaging specification	SOP-Y-3382
接线方式/Terminal	Crimping
螺丝扭矩/Tightening torque(N·m/Lb.in)	M12x1.0, 3~4kgf.cm
	M17x1.0, 4~6kgf.cm
线径范围/Wire range(AWG/mm²)	24~20/0.25~0.5

		MATERIAL:		SURFACE/COLOR:	
		MAT NO./REV: 20030002361-1 / 00		MAT STATUS: 批量	
APPD:		NAME PC-M12A-04P-MM-SR7001-00A (H)			
CHKD:					
DRFT:					
A4		DRAWING NO. 200108723	TYPE CUSTOMER DRAWING	DRAWING STATUS work	SCALE 2:1
		SHEET 1/1			

00	ECN	DESCRIPTION	DRFT	DATE
REV	ECN	DESCRIPTION	DRFT	DATE

1

2

3

4

5

6