


Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非经书面确认，否则禁止转让、复制、利用、交流本文件的内容。侵犯者将负赔偿责任。本公司保留对涉及发明、实用新型和外观专利的所有权利。





其他接线方式：

形式一：




ESS-50A-06-X-XX-00


Color: BK:Black 负极
OR:Orange 正极
RD:Red 正极


Contact Termination:B:Busbar
C:Crimp
S:Screw
B/S:Copper Screw

形式二：



形式三：






Recommended
Panel Cut-Out

尺寸公差(mm)					
0 ~ 30	>30 ~ 60	>60 ~ 100	>100 ~ 150	>150	0.05/10
±0.20	±0.30	±0.50	±0.70	±1.00	±1°

技术要求/Technical requirements:	
颜色/Color	Black,Orange,Red
锁紧方式/Locking method	卡扣(Buckle)
接线方式/Terminal	Busbar,Screw,Crimp,Copper Screw
外壳材料/Housing materrial	PA+GF
接触件材料/Connector materrial	铜合金(Copper alloy)
插入力/Insertion force	65N Max
拔出力/Withdrawal force	＞10N
插拔次数/Mechanical working life(mating cycles)	100
安装螺母紧固扭矩/Screw torque	M4/0.4~0.7N.m
接线规格/Wiring specifications	10AWG or 6mm²
建议剥线长度/Suggested stipping length	7~8mm（Crimp type）
额定电压/Rated voltage	1000V DC
额定电流/Rated current	50A
绝缘电阻/Insulate resistance	≥500MΩ(drying)
耐电压/Withstanding voltage	4250V/min
接触电阻/Contact resistance	≤0.5mΩ
过电压等级/Overvoltage category	III
污染等级/Pollution degree	3
防护等级/Ingress protection	IP67(Mated)
使用温度范围/Operating temperature(° C)	-40~+125(including temperature rise)
盐雾/Salt spray	48H
储存温度/Storage temperature(° C)	-40~+85
阻燃等级/Flame retardant ability	UL94-V0
符合RoHS环保要求/Conform to RoHS	Yes
UL4128认证/UL4128 certification	E526028
TUV认证/TUV certification	50581738
满足户外使用/Satisfy outdoor use	Yes

仅Busbar的形式3D展示：



REV	ECN	DESCRIPTION	DRFT	DATE
01				

DEGSON

APPD:	刘剑	2024.01.24
CHKD:	于进海	2024.01.21
DRFT:	张晓瑶	2024.01.17

A4 mm (inch)

MATERIAL:		SURFACE/COLOR:	
MAT NO./REV:	/	MAT STATUS:	
NAME	ESS-50A-06-X-XX-00		
DRAWING NO.	TYPE	DRAWING STATUS	SCALE / SHEET
200269245	CUSTOMER DRAWING		1:1 / 1/1