

## Overview

### Product information



**Relay base-DPSF06A-E3-00A(H)-30020000065**

DPSFrelay base,used for1PDTrelay,screw connection

### Product advantages

- ☑ Plug-in relay socket
- ☑ Safe isolation between coil and contacts
- ☑ 6A, 1PDTgrade
- ☑ Arc partition between adjacent columns
- ☑ Anti-touch cover at the top of the screw

### Product certification

## Technical data

### Product drawing

### 3D model

□

### Environmental data

Ambient temperature (operation)

-40℃～+70℃

Ambient temperature (storage / transport)

-40℃～+70℃

### Technical data

Rated voltage UN

300V

Installation location

Arbitrary

Assembly instructions

DIN35 rail

### Connection data 1

Connection name

enter

Connection method

Screw connection

Stripping length	7-8mm
screw thread	M3
Cross section of flexible conductor	0.5... 2.5mm <sup>2</sup>
Connectable guide cross section AWG	20-14AWG

#### Connection data 2

Connection name	Output
Stripping length	7-8mm
Cross section of flexible conductor	0.5... 2.5mm <sup>2</sup>
Connectable guide cross section AWG	20-14AWG
Connection method	Screw connection

#### Dimension

length	96.5mm
width	6.2mm
Depth including bracket	81mm

#### Accessories

#### Business data

Order number	30020000065
Packing unit	20 SKT
Minimum order quantity	20 SKT
Products weight (without packaging)	56g