

Overview

Product information



9EDGKS-10.16-10010009754

Pluggable terminal blocks,Rated current:78.3A.Rated voltage (III/2) :1000V,pitch:10.16mm,Color:black,Contact surface :Ag

Product advantages

- $\ensuremath{\mbox{$\sc Z$}}$ Screw connection technology, safe and reliable
- ☑ Meet group C 600 V requirements of UL1059 standard
- ☑ Meet the requirements of IEC 61800-5-1 for electric shock protection
- \square The design of the middle flange reduces the space of at least one circuit compared to other soultions.

Product certification



Technical data	
Product drawing	
3D model	
Packaging information	
Type of packaging	box-packed
Climatic test	
IP class	IP20
Connection capacity	
Conductor cross section solid	0.2~16mm²
Conductor cross section flexible	0.2~16mm²
feeler gauge a x b / diameter	4.3mm x4.0mm/5.2mm
AWG	22~6AWG

Torque	1.5N.m
Strip length	12mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	57A
Rated current (D)	5A
Rated current (C)	57A

Electrical parameters IEC

Rated voltage	1000V
Rated voltage(III/3)	1000V
Rated current	78.3A
Rated voltage(III/2)	1000V
Rated voltage(Il/2)	1000V
Rated surge voltage(III/3)	8KV
Rated surge voltage(III/2)	8KV
Rated surge voltage(II/2)	6KV

Item properties

Connection direction	0°
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M4
Pitch	10.16mm
Number of potentials	2

Pluggable or not	Yes
Number of rows	1
aterial data	
Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	Silver plated
Contact zone metal surface	Silver plated
Insulation Materials	PA66
Relative tracking index CTI	600V
Shell color	Black
Insulating material group	I
Flammability rating	UL94V-0
lechanical tests	
Test Specification	IEC61984/ UL1059
vironmental data	
Ambient temperature (operation)	-40°C~120°C(depending on derating curve)

cessories	
Tool	
Screwdriver	0.8x4.5, Slotted screwdriver
Operating tool	
Accessories	
Coding strip	1
Bridge	1
Marking strip	

Others	/
--------	---

Business data	
Order number	10010009754
Packing unit	70
Minimum order quantity	
Products weight (without packaging)	30.77