

Overview		
Product information		
Z LO	Pluggable terminal bl	62-200Z-10060008664 locks,Reversed pin,Rated current:41A.Rated voltage .62mm,Color:Green,Contact surface :Tin
Product advantages		
 Well-known mounting principle allor Adopting a high protection design, Keying parts can be installed 		ection for device output or PCB to PCB connections
Product certification		
c FU ® us		
Technical data		
Product drawing		
3D model		
٥		
Packaging information		
Type of packaging		box-packed
Processing notes		
Process		Wave soldering/manual soldering
Electrical parameters UL		
Rated voltage (B)		300V
Rated voltage (C)		300V
Rated voltage (D)		600V
Rated current (B)		41A
Rated current (D)		5A

Rated current (C)	41A
ectrical parameters IEC	
Rated voltage	800V
Rated voltage(III/3)	630V
Rated current	41A
Rated voltage(III/2)	800V
Rated voltage(II/2)	800V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV
m properties	
Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Three rows in a straight line
Pitch	7.62mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1
aterial data	
Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact zone metal surface	tin-plated

600V

Relative tracking index CTI

Glow Wire Flammability Index GWFI	850
Glow wire ignition temperature GWIT	750
Ball pressure test temperature	125 ℃
Shell color	green
Insulating material group	Ι
Flammability rating	UL94V-0
lechanical tests	
Test Specification	UL1059/IEC60998
invironmental data	
Ambient temperature (operation)	-40 °C~105 °C(depending on derating curve)

Accessories	
Tool	
Screwdriver	1
Operating tool	1
Accessories	
Coding strip	5EDG-PWI
Bridge	1
Marking strip	1
Others	1

Business data	
Order number	10060008664
Packing unit	330
Minimum order quantity	

|--|