

Overview

Product information



2EDGKGB-5.08-10010010143

Pluggable terminal blocks,Rated current:12A.Rated voltage (III/2):400V,pitch:5.08mm,Color:green,Contact surface:Tin

Product advantages

- $\ensuremath{\square}$ Well-known mounting principle allows worldwide use
- ☑ Adapt to multi-type sockets, device design is highly flexible
- $\ensuremath{\square}$ Both sides with operating rods, easy to pull out

Product certification

_		
1 60	hnical	data

Product drawing

3D model

Packaging information

Type of packaging	bag packaging
-------------------	---------------

Connection capacity

Conductor cross section solid	0.2~2.5mm²
Conductor cross section flexible	0.2~2.5mm²
feeler gauge a x b / diameter	2.8mm x2.4mm/2.5mm
AWG	28~12AWG
Torque	0.5N.m
Strip length	7mm

Electrical parameters UL

Rat	ed voltage (B)	300V
-----	----------------	------

Rated voltage (D)	300V
Rated current (B)	15A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	400V
Rated voltage(III/3)	320V
Rated current	12A
Rated voltage(III/2)	400V
Rated voltage(II/2)	630V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

Item properties

Connection direction	0°
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	МЗ
Pitch	5.08mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated

Contact zone metal surface	tin-plated	
Insulation Materials	PA66	
Shell color	green	
Insulating material group	I	
Flammability rating	UL94V-0	
Mechanical tests		
Test Specification	IEC61984/ UL1059	
Environmental data		
Relative humidity (storage/transport)	30% ~ 70%	
Ambient temperature (assembly)	-5℃~100℃	
Ambient temperature (operation)	-40°C~105°C(depending on derating curve)	
Ambient temperature (storage / transport)	-40℃~70℃	

ool	
Screwdriver	0.6x3.5,Slotted screwdriver
Operating tool	1
ccessories	
Coding strip	2EDG-PWI
Bridge	DG019-5.0
Marking strip	

Business data	
Order number	10010010143
Order number	10010010143

Packing unit	100
Minimum order quantity	
Products weight (without packaging)	4.65