

Product information		
	Sensor/Actuator Fema	P-MM-SF7003-20030001353 ale socket,M12,Coding B,Unshielded,Rear panel hread mounted,90° horizontal pins
Product advantages		
☑Sealing optimization, protection lev ☑Meet the harsh environment ☑Suitable for various occasions cor ☑Compatible with the international a	nection technology	products
Product certification		
	RFACH .9	®
Product drawing		
Product drawing 3D model		
Product drawing 3D model		
echnical data Product drawing 3D model Environmental conditions Ambient temperature		-40℃105℃
Product drawing 3D model Environmental conditions		-40℃105℃ IP67
Product drawing 3D model Environmental conditions Ambient temperature		
Product drawing 3D model a Environmental conditions Ambient temperature IP class General parameters		
Product drawing 3D model Environmental conditions Ambient temperature		IP67
Product drawing BD model Environmental conditions Ambient temperature IP class General parameters		IP67 4A

 Insulation resistance
 ≥ 100 MΩ

 Error-proof coding
 B-Code

Overvoltage level	П
Pollution level	3
Connection method	Soldering pin
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm
Type of installation	Rear board installation

Material

Flammability rating ,in line with UL94	VO	
Contact material	CuZn	
Material contact surface	Au	
Contact carrier material	PA	
Coil material	Zinc alloy, nickel plated	
Sealing material	Silicon	
Standards and specifications		
Standards/specifications	IEC 61076-2-101	

Accessories	
Accessories	
Sealing cap	CAP-M12-FP-8003

Business data		
Order number	20030001353	
Packing unit	/	
Minimum order quantity	100	
Products weight (without packaging)	1	