

Overview		
Product information		
	Sensor/Actuator Cab	4P-MM-SR8C01-20030000671 ble,PVC,black,UL2517,Male plug,acodado M12,Coding ng cable end,Unshielded,Cable Cable length:1m,UL
Product advantages		
 Sealing optimization, protection le Meet the harsh environment Suitable for various occasions cor Compatible with the international and 	nnection technology	products
Product certification		
	REACH .5	
Technical data		
Product drawing		
3D model		
Environmental conditions		
Ambient temperature		-25 ℃ 85 ℃
IP class		IP68
General parameters		
Rated current		4A
		250V
Number of potentials		4
Insulation resistance		≥ 100 MΩ
Error-proof coding		A-Code

Overvoltage level	II
Pollution level	3
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm

Material

Flammability rating ,in line with UL94	VO
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Fixture body material	TPU
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-101
--------------------------	-----------------

Cable

Cable type	PVC Black
Cable type(abbreviation)	PVC
UL AWM form	UL2517
Cross section	0.34mm²
AWG signal wire	22AWG
Wire structure Signal wire	17/0.16mm ²
Core diameter (including insulation layer)	1.30±0.05mm
Wire color	1 Brown 2 White 3 Blue 4 Black
Thickness, insulation	0.6mm
Cable outer diameter D	5.0 ±0.2mm

Outer sheath, material	PVC
Conductor insulation material	PVC
Conductor material	Tinned copper
Insulation resistance	≥100MΩ
Conductor resistance	Maximum 59.4Ω/km (at 20 °C))
Nominal cable voltage	300∨
Cable test voltage	2000∨
Flame retardant	Comply with UL 758/1581 FT1 standard
Halogen free	Yes
mension	
Cable length	1m

Accessories	
Accessories	
Sealing cap	CAP-M12-FP-8001

Business data	
Order number	20030000671
Packing unit	/
Minimum order quantity	100
Products weight (without packaging)	/