

Overview		
Product information		
	PCB terminal blocks, section:0.2-6.0mm²,p	5-10040000758 Rated current: 32A,Rated voltage (III/2) 630V,Cross hitch:6.35mm,connector method:Screw connector with green,Contact surface :Tin
Product advantages		
 Fixed screw connection technolog Different poles can be combined t Universal installation method to er 	hrough the side lock	xibility in device design
Product certification		
c SN [®] us		
echnical data		
Product drawing		
3D model		
•		
Processing notes		
Process		Wave soldering/manual soldering
Connection capacity		
Conductor cross section solid		0.2~6mm²
Conductor cross section flexible		0.2~6.0mm ²
AWG		30~10AWG
Torque		0.8N.m
Strip length		8mm
Electrical parameters UL		

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	30A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	630V
Rated voltage(III/3)	500V
Rated current	32A
Rated voltage(III/2)	630V
Rated voltage(II/2)	1000V
Rated surge voltage(III/3)	6KV
Rated surge voltage(III/2)	6KV
Rated surge voltage(II/2)	6KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3.5
Pitch	6.35mm
Number of potentials	4
Pluggable or not	no
Number of rows	2

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	Ι
Flammability rating	UL94V-0
Nechanical tests	
Test Specification	IEC60947/UL1059
Environmental data	
Ambient temperature (operation)	-40℃~105℃(depending on derating curve)

ccessories	
Coding strip	/
Bridge	
Marking strip	/
Others	/
ool	
Operating tool	/
Screwdriver	0.6x3.5mm, Slotted screwdriver

Business data	
Order number	10040000758
Packing unit	220
Minimum order quantity	30

Products weight (without	
packaging)	