

## Overview

#### **Product information**



# DG381-THR-3.5-10040002112

PCB terminal blocks,Rated current: 13.5A,Rated voltage (III/2) 200V,Cross section:0.2-1.5mm²,pitch:3.5mm,connector method:Screw connector with tension sleeve,Color:black,Contact surface:Tin

## Product advantages

- $\ensuremath{\square}$  Universal installation method to ensure a high degree of flexibility in device design
- ☑ Suitable for SMT welding process
- ☑ Fixed screw connection technology,safe and reliable

#### Product certification



Tec	hnical	data

_		
Prod	LICT	drawing
	uot	araving

3D model

## Processing notes

Process	Reflow soldering/wave soldering/manual soldering
---------	--

## Connection capacity

Conductor cross section solid	0.2~1.5mm²
Conductor cross section flexible	0.2~1.5mm²
AWG	30~16AWG
Torque	0.2N.m
Strip length	5mm

## Electrical parameters UL

Rated voltage (B)	150V
Rated current (B)	10A

## Electrical parameters IEC

Rated voltage	200V
Rated voltage(III/3)	63V
Rated current	13.5A
Rated voltage(III/2)	200V
Rated voltage(II/2)	200V
Rated surge voltage(III/3)	2.5KV
Rated surge voltage(III/2)	2.5KV
Rated surge voltage(II/2)	2.5KV

## Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M2
Pitch	3.5mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

# Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy

Contact point metal surface	tin-plated		
Insulation Materials	High temperature resistant materials		
Insulating material group	IIIa		
Flammability rating	UL94V-0		
Mechanical tests			
Test Specification	IEC60947/UL1059		
Environmental data			
Ambient temperature (operation)	-40°C~130°C(depending on derating curve)		

ccessories	
Coding strip	1
Bridge	1
Marking strip	
Others	1
ool	
Operating tool	
Screwdriver	0.4x2.5mm, Slotted screwdriver

usiness data	
Order number	10040002112
Packing unit	1500
Minimum order quantity	30
Products weight (without packaging)	1.03