

## Overview

### Product information



### DG380A-3.81-10040001360

PCB terminal blocks, Rated current: 12A, Rated voltage (III/2) 320V, Cross section: 1.5mm<sup>2</sup>, pitch: 3.81mm, connector method: Screw connector with tension sleeve, Color: green, Contact surface : Tin

### Product advantages

- ☒ Universal connection method to ensure a high degree of flexibility in device design
- ☒ Multi-layer wire connection can achieve higher contact density
- ☒ Fixed screw connection technology, safe and reliable

### Product certification



## Technical data

### Product drawing

### 3D model

□

### Processing notes

Process

Wave soldering/manual soldering

### Connection capacity

Conductor cross section solid

0.2~1.5mm<sup>2</sup>

Conductor cross section flexible

0.2~1.5mm<sup>2</sup>

AWG

30~14AWG

Torque

0.2N.m

Strip length

6mm

### Electrical parameters UL

Rated voltage (B)	300V
Rated current (B)	12A

#### Electrical parameters IEC

Rated voltage	320V
Rated voltage(III/3)	200V
Rated current	12A
Rated voltage(III/2)	320V
Rated voltage(II/2)	500V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

#### Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M2
Pitch	3.81mm
Number of potentials	4
Pluggable or not	no
Number of rows	2

#### Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy

Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

#### Mechanical tests

Test Specification	IEC60947/UL 1059
--------------------	------------------

#### Environmental data

Ambient temperature (operation)	-40°C~105°C(depending on derating curve)
---------------------------------	--

### Accessories

#### Accessories

Coding strip	/
Bridge	DG032-3.81
Marking strip	/
Others	/

#### Tool

Operating tool	/
Screwdriver	0.4x2.5mm, Slotted screwdriver

### Business data

Order number	10040001360
Packing unit	1200
Minimum order quantity	30
Products weight (without packaging)	2.83

