


## Overview

## Product information

**DG242V-7.5-10060001172**

PCB spring terminal blocks, Rated current: 17A. Rated voltage  
(III/2) : 750V, pitch: 7.5mm, Color: gray, Contact surface : Tin

## Product advantages

- ☑ Cage clamp connection technology, fast wiring
- ☑ Different poles can be combined through the side lock
- ☑ Universal installation method to ensure a high degree of flexibility in device design

## Product certification



## Technical data

## Product drawing

## 3D model

□

## Processing notes

Process

Wave soldering/manual soldering

## Connection capacity

Conductor cross section solid

0.2~2.5mm<sup>2</sup>

Conductor cross section flexible

0.2~2.5mm<sup>2</sup>

AWG

28~12AWG

Strip length

6mm

## Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

Rated current (B)	15A
Rated current (D)	10A

#### Electrical parameters IEC

Rated voltage	750V
Rated current	17A
Rated voltage(III/2)	750V
Rated power frequency voltage(1min)	3KV

#### Item properties

Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	spring-cage connection
Pitch	7.5mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

#### Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

#### Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data
--------------------

Ambient temperature (operation)	-40°C~105°C(depending on derating curve)
---------------------------------	--

Accessories
-------------

Accessories
-------------

Coding strip	/
--------------	---

Bridge	/
--------	---

Marking strip	/
---------------	---

Others	/
--------	---

Tool
------

Operating tool	/
----------------	---

Screwdriver	/
-------------	---

Business data
---------------

Order number	10060001172
--------------	-------------

Packing unit	800
--------------	-----

Minimum order quantity	30
------------------------	----

Products weight (without packaging)	2.949
-------------------------------------	-------