


Overview

Product information



DG238-10.0-10060000985

PCB spring terminal blocks, Rated current: 24A. Rated voltage
(III/2) : 450V, pitch: 10.0mm, Color: White, Contact surface : Tin

Product advantages

- ☒ Multiple wiring holes for current distribution
- ☒ Panel mounting, suitable for various situations
- ☒ Can realize horizontal wire-to-wire connection

Product certification



Technical data

Product drawing

3D model

□

Connection capacity

AWG	22~14AWG
Strip length	9mm

Electrical parameters UL

Rated voltage (B)	600V
Rated current (B)	20A

Electrical parameters IEC

Rated current	450V
	24A
Rated voltage(III/2)	450V

Rated power frequency voltage(1min)	2.5KV
-------------------------------------	-------

Item properties

Connection method	Push-in spring connection
Pitch	10mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-2

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~105℃(depending on derating curve)
---------------------------------	--

Accessories

Accessories

Coding strip	/
Bridge	/
Marking strip	/

Others	/
--------	---

Tool

Operating tool	/
Screwdriver	/

Business data

Order number	10060000985
Packing unit	100
Minimum order quantity	30
Products weight (without packaging)	6.25