


Overview

Product information



8EDG-STDBM-5.0-10020003182

Pluggable terminal blocks, Rated current: 20A, Rated voltage
(III/2) : 320V, pitch: 5.0mm, Color: gray, Contact surface : Tin

Product advantages

- ✓ Can achieve 90° transfer connection
- ✓ Cage clamp connection technology, fast wiring
- ✓ Panel or through-wall mounting, suitable for various situations

Product certification



Technical data

Product drawing

3D model

Connection capacity

Conductor cross section solid	0.2~2.5mm ²
Conductor cross section flexible	0.2~2.5mm ²
AWG	22~14AWG
Strip length	7mm

Electrical parameters UL

Rated voltage (B)	300V
Rated current (B)	15A

Electrical parameters IEC

Rated voltage	320V
---------------	------

Rated current	20A
Rated voltage(III/2)	320V
Rated surge voltage(III/2)	4KV

Item properties

Connection direction	45°
Pin arrangement	Single row in a straight line
Pitch	5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40℃~105℃(depending on derating curve)
---------------------------------	--

Accessories

Accessories

Coding strip	/
Bridge	DG018-5.0
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Business data

Order number	10020003182
Packing unit	100
Minimum order quantity	30
Products weight (without packaging)	3.5