

Overview

Product information



2EDG-UDB-5.08-10010002836

Pluggable terminal blocks,Rated current:12A.Rated voltage (III/2):320V,pitch:5.08mm,Color:green,Contact surface:Tin

Product advantages

- $\ensuremath{\mbox{$\sc\sc{Z}$}}$ Adapt to multi-type plugs, device design is highly flexible
- ☑ Keying requirements can be met
- ☑ Din rail installation, suitable for various situations

Product certification



Technical data

Prod	luct	dra	wina
FIUU	ucı	ula	wiiiu

3D model

Processing notes

Process	Wave soldering/manual soldering	

Connection capacity

Conductor cross section solid	0.2~2.5mm²
Conductor cross section flexible	0.2~2.5mm²
AWG	28~12AWG
Torque	0.6N.m
Strip length	7mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	320V
Rated voltage(III/3)	250V
Rated current	12A
Rated voltage(III/2)	320V
Rated voltage(II/2)	630V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

Item properties

Connection direction	0°
Type of installation	Rail mounting
Pin arrangement	Single row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	5.08mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS	
Contact material	copper	
Contact point metal surface	tin-plated	
Contact zone metal surface	tin-plated	
Insulation Materials	PA66	
Insulating material group	I	
Flammability rating	UL94V-0	
Mechanical tests		
Test Specification	IEC61984/ UL1059	
Environmental data		
Ambient temperature (operation)	-40℃~105℃(depending on derating curve)	

ool	
Screwdriver	0.6x3.5, Slotted screwdriver
Operating tool	I I
ccessories	
Coding strip	2EDG-PWP
	1
Bridge	
Bridge Marking strip	1

Business data	
10010002836	
315	

Minimum order quantity	30
Products weight (without packaging)	8.73